

TOE-MN / MA / MI Series

*Heat transfer pumps
for heat transfer oils up to 350 °C*

*with magnetic coupling
volute casing PN 16
bearing brackets 360 and 470*

Pumps for heat transfer technology

Main applications

- » Tempering in plastics and die cast industry
- » Baking ovens, large frying units as well as in the production of edible oils and dry masses for the food and feedstuff industries
- » Heating calenders and melting pots in the leather and rubber industry
- » Heating stirring and mixing vessels in the production of paints and varnishes
- » Heating tank storage facilities on stationary and FPSE platforms as well as in tankers
- » Heating press lines in the wood and pulp industry
- » Flat glass production
- » Solar power stations and ORC processes

Usage

These pumps are designed for circulating organic or synthetic heat transfer oils in heat transfer plants in acc. with DIN 4754.

Suitable for media to be pumped with little non-abrasive contaminations

	Spheroidal graphite cast iron version	Stainless steel version
Media	Heat transfer oil / thermal oil	Heat transfer oil / thermal oil
T _{min}	- 40 °C	- 100 °C
T _{max}	+ 350 °C	+ 250 °C
Casing	Spheroidal graphite cast iron EN-GJS-400-15 (GGG-40)	Stainless steel 1.4581
Nominal pressure	PN 16	
H _{max} (2900 min ⁻¹)	100 m	60 m
Q _{max} (2900 min ⁻¹)	550 m ³ /h	170 m ³ /h
ATEX		II 2G c b TX

Denomination

Type code Example	TOE-	M	A-	32-	160	/150
Denomination of series						
Magnetic coupling						
N = Version with bearing bracket, volute casing ax/top						
A = Close-coupled version with bracket, volute casing ax/top						
I = Close-coupled version with bracket, inline casing						
Nominal width of outlet nozzle DN						
Nominal impeller diameter in mm						
Actual impeller diameter in mm						

Your contacts

**Speck Pumpen
Systemtechnik GmbH**
Regensburger Ring 6 -8
91154 Roth
Tel: +49 9171 809-0
Fax: +49 9171 809-10
info@speck.de
www.speck.de

International representatives
→ page 51

TOE-MN / MA / MI Series

	TOE-MN	TOE-MA	TOE-MI
	 <p>Example: Casing with feet</p>	 <p>Example: Casing with centreline mounting</p>	 <p>H</p>
Features	<ul style="list-style-type: none"> » Bearing bracket / process design » Base plate » Dismantling of the bearing bracket possible without moving the motor » Alignment / checking of the coupling required before start-up » Pump and aggregate dimensions in acc. with EN 733 	<ul style="list-style-type: none"> » Bracket version » Base plate optional » No alignment of coupling required before start-up » Space for disassembling the cartridge insert required » Pump dimension in acc. with EN 733 	<ul style="list-style-type: none"> » Bracket version with inline casing » No alignment of coupling required before start-up » Space for disassembling the cartridge insert required
Pump dimensions	→ Pages 16 and 17	→ Pages 16 and 17	→ Page 18
Hydraulics and casing	<ul style="list-style-type: none"> » Identical hydraulics fo TOE-MN and TOE-MA Characteristic curves → pages 12 and 13 » Identical volute casing for each frame size » Large pumps with centreline mounting and double volute Description → page 5 		<ul style="list-style-type: none"> » Characteristic curves → pages 12 and 13 » Inline casings with two dimensions H available
Sizes	Only two bearing brackets for all sizes <ul style="list-style-type: none"> » Bearing bracket 360 for 12 sizes - identical and interchangeable » Bearing brackets 470 for 7 sizes - identical and interchangeable » Only one bracket per size 		
Description	Material versions and design → pages 6 and 7		
Interchangeability of parts	<ul style="list-style-type: none"> » Within all series including the versions with magnetic coupling (→ see catalogue TOE-GN/GA/GI) there is a high degree of interchangeability. » This means minimum spare parts stock and full flexibility as replacing pumps or components or retrofitting to a different design is very easy. » Table of interchangeable parts → page 19 		

High operational safety, optimal design and service-friendly

Robust design

Torsion-resistant casing cover and ball bearings with lifetime lubrication

Wearing-resistant SiC sleeve bearing

Solid, hydrodynamically lubricated sleeve bearings made from SiC as tried-and-tested slide material - extremely wear-resistant and good resistance in corrosive media.

Impellers with back vanes

The back vanes of the impellers significantly reduce the axial thrust and therefore remove strain from the axial bearings considerably. They also keep dirt particles away from the sleeve bearings.

Clever temperature management

Optimised cooling of ball bearings and magnetic coupling

A fan blade on the coupling is also used for cooling in the TOE-MN series. Here, the generated air flow, in combination with coupling protection, ventilation slots and cooling zone, reduces the temperature on the magnetic coupling and ball bearings extremely effectively.

On close-coupled pumps of the TOE-MA and TOE-MI series, the motor fan also cools the bearing shield and therefore also the ball bearings inside it.

Also suitable for critical applications

Pumps with magnetic couplings

100% free of leakage and lower maintenance requirements than pumps with mechanical seals.

Start-up safety device

Two start-up safety devices on the inner and outer rotor avoid the destruction of the separating can if a sleeve or rolling bearing fails and they ensure that the pump remains hermetically sealed.

ATEX

All magnetically-coupled pumps are ATEX certified.

Optimal design

Energy efficiency

High energy efficiency secures a lasting competitive edge.

Speck offers the important criteria for energy-optimised design. Seamless range of sizes, highly efficient impellers, switching of impellers for the best design at the operating point and, naturally, motors in accordance with IE2.

Optimal sizes of magnetic couplings

Magnetic couplings in staged sizes guarantee optimal design at the operating point with minimal viscosity and eddy current losses.

Maintenance-friendly and flexible

Simple installation

All series are extremely maintenance-friendly thanks to easy-to-remove bearing brackets.

You can replace the sleeve bearing cartridge easily as a complete spare part. It is quick and ensures correct installation every time.

Minimum spare parts stock

The high level of interchangeability of identical parts guarantees minimal spare parts stock requirements and an extremely high level of flexibility.

Retrofitting to a different series is also no problem at all - the volute casing can even be left in the system.

Safe

The separating can remains hermetically sealed at bearing failures thanks to start-up safety devices.

Robust and service-friendly

Solid sleeve bearing cartridge with SiC - can be replaced as a complete spare part

Temperature management

Several ventilation slots
Cooling zone
Fan blades (TOE-MN only)





Figure: TOE-MN, bearing bracket 470, casing with centreline mounting

Longer lifetime

There are effects, which have little or no relevant impact on smaller designs, but lead to increased wear in larger pumps.


Speck offers larger pumps with special designs to guarantee a longer lifetime: Casing with centreline mounting and double volute.

Centreline mounting relieves strain from the bearings and coupling



Casings with feet: The larger the pump, the more strain placed on the bearings and magnet coupling by heat expansion.

Casings with feet can only expand upwards in high temperatures, which causes the pump to tilt and bend. This has an impact on the magnetic coupling and the shaft coupling in particular. As the heat expansion increases with larger casing sizes, the shaft couplings and, eventually the safety start-up devices, wear faster on larger pumps.




The centreline mounting eliminates the impact of the heat expansion completely.

Speck is the only manufacturer to use a centreline mounting for heat transfer pumps volute casings (PN 16). It eliminates the impact of vertical expansion completely. The shafts are always aligned at optimal height, even in hot operation. The shaft coupling achieves a significantly higher lifetime and intact start-up safety devices still work if bearing failures occur.

A double volute remove strain from the sleeve bearings

Radial forces are applied directly on the sleeve bearings. The forces increase with higher impeller diameters and higher speeds. This is why the sleeve bearings on larger pumps with single volute casings wear faster.

Speck therefore uses casings with double volute for larger pumps, which significantly reduce the radial forces. The strain on the radial and axial bearings is considerably reduced, helping them achieve a much longer lifetime.



TOE-MN / MA – Sizes and casing designs



32-160*	40-160	50-160	65-160	80-160	100-160	-
32-200*	40-200*	50-200*	65-200*	80-200	100-200	125-200
32-250	40-250	50-250	65-250	80-250	100-250	-
Bearing bracket 360				Bearing bracket 470		

* also available in stainless steel version


All casings with dimensions in accordance with EN 733 Casing with double volute Casing with centreline mounting

Material designs


TOE-MN

Bearing bracket 360
with Ø 250 mm impeller

TOE-MA



TOE-MI



	Spheroidal graphite cast iron version	Stainless steel version
Media	Heat transfer oil / thermal oil	Heat transfer oil / thermal oil
T _{min}	- 40 °C	- 100 °C
T _{max}	+ 350 °C	+ 250 °C
Nominal pressure	PN 16	
ATEX	II 2G c b TX	
Series	All series	TOE-MN, MA series
Sizes	All sizes	32-160 32-200 40-200 50-200 65-200
H _{max} (2900 min ⁻¹)	100 m	60 m
Q _{max} (2900 min ⁻¹)	550 m ³ /h	170 m ³ /h

No.	Designation	Spheroidal graphite cast iron version	Stainless steel version
1	Impeller	EN-GJL-250	1.4581
2	Casing	EN-GJS-400-15	1.4581
3	Casing cover	EN-GJS-400-15	1.4581
4	Shaft	1.4122	1.4571
5	Sleeve bearing	SiC	SiC
6	Inner magnet	Sm ₂ Co ₁₇	Sm ₂ Co ₁₇
7	Outer magnet	Sm ₂ Co ₁₇	Sm ₂ Co ₁₇
8	Separating can	2.4610	2.4610

No.	Designation	Spheroidal graphite cast iron version	Stainless steel version
9	Bracket	EN-GJS-400-15	EN-GJS-400-15
10/1	Drive shaft / motor shaft	1.4122	1.4122
11	Coupling insert	EN-GJL-250	EN-GJL-250
12	Bearing casing	EN-GJL-250	EN-GJL-250
13	Rolling bearing	High-quality brand	High-quality brand
14	Counter flange	EN-GJS-400-15	EN-GJS-400-15

EN-GJL-250 = GG-25, EN-GJS-400-15 = GGG-40

Design

Magnetic couplings

The magnetic coupling consist of inner magnetic rotor, separating can and outer magnetic rotor.

The large numer of staged sizes and a modern design software guarantee the best design at the operating point. The transmissible torques of the magnetic couplings range between 10 and 500 Nm.

Type code

Type code Example	135-	70
Nominal diameter DN		
Magnetic length [mm]		

Magnetic coupling sizes

Magnetic length [mm]	Magnetic coupling diameter				
	DN 60	DN 75	DN 110	DN 135	DN 165
40	x	x	x		
50		x	x	x	
60	x	x	x	x	
70			x	x	
80			x	x	x
90				x	x
100					x
110					x
120					x
	360	360	360, 470	360, 470	470
			Bearing bracket		

Maintenance-friendly and safe design

Assemblies are easy-to-replace spare parts

The cartridge insert (TOE-MN) or assembly unit (TOE-MA, TOE-MI) are the parts of the pump getting in touch with the medium to be pumped. They can be removed easily from the volute casing without dismantling the pipes. Both are available as a single spare part and the best choice for quick and falseless repair. We recommend to put at least one cartridge insert/assembly unit into stock.

Further subassemblies are designed in the same way. In the event of servicing, they can be ordered and replaced as a single spare part.


Flushing bore holes

Current eddy, viscosity and bearing friction losses lead to higher temperatures within the pump and have to be added to the media temperature. Flushing bore holes in the inner rotor and the casing ensure that these critical places are cooled by the medium to be pumped. In addition, light ends are discharged from the inner rotor.

Temperature control

If required (e.g. in potentially explosive areas), temperature sensors can be installed in the bracket to control the surface temperature of the separating can.

Assemblies



Simple and optimal configuration software

SPAIX selection program

The screenshot shows the SPAIX selection program interface. On the left, a sidebar lists pump types: 'Gesamtprogramm' (high head pump, MZ, side channel pump, TOE-M stainless steel, heat transfer engineering). A red box highlights the 'heat transfer engineering' option. Below it, a list of pump models is shown, with 'TOE-M / TOE-MI' selected (indicated by a checked checkbox). A red box highlights this selection. To the right, a table titled 'Pump selection' shows various parameters like flow rate, head, and temperature for different pump models. A red box highlights the first row of the table.

The software allows you to configure heat transfer pumps, side channel pumps and boiler feed pumps via your Internet browser. As well as design details, the system will also request operating details and details about the medium to be pumped.



Characteristic curve depending on hydraulic selection

Ideal for system planners

Speck now also offers the latest version 4 of the renowned SPAIX design software.

We make the program available to authorised customers who can pre-select the pumps within their system.

The web-based software always accesses an up-to-date database.

Easy pre-selection

The configuration system avoids a wide range of selection parameters with regard to design, sealing systems, hydraulics, operating conditions and media.

The software has language options for German and English.

Checking the pre-selection

When the order is submitted, the customer's choices are double-checked to ensure that your project requirements are met.


Key

- 1** List of all pump designs that can be configured in the software
- 2** List of all series within the pump designs
- 3** Selection parameters operating parameters and medium data in the first instance
- 4** Characteristic curve depending on hydraulic selection generated


Documentation based on the selection program

Data Sheet				Confirmation of order Projekt 2015-08-18 09:			
Heat transfer pump TOE-MA 032-250				Created on 2015-08-18 Item Rev.: 2015-08-18 Page 2 / 4			
SPECK PUMPEN Systemtechnik GmbH Regensburger Ring 6 - 8 D-91154 Roth Tel.: 09171/809-0 Fax: 09171/809-10 www.speck-pumps.de							
Customer	Speck Systemtechnik			Kontakt	Editor		
City	---			Phone	Phone		
Enquiry	vom			Fax	Fax		
Project				E-mail	E-mail		
Operating Data							
1 Fluid	Marlotherm SH	Flow rate	rated 25,09 m ³ /h	Speed	2900 1/min		
2 corrosive matters	keine/not	Wght.-%	min / max 3,9 / 48,8 m ³ /h	Efficiency	38,96 %		
3 abrasive matters	keine/not	Wght.-%	Pressure inlet 0 bar (u)	Total abs. power	8,85 kW		
4 Solids	0 Wght.-%		Disch. 5,005 bar (u)	Dissipation	2,582 kW		
5 Oper. Temp. tW / tS	300 / 20 °C	Head	60,44 m				
6 Density at tW / tS	844,1 / 1044 kg/m ³	Pressure differential	5,00 bar (u)				
7 Kin. viscosity at tW / tS	0,4499 / 47 mm ² /s			Flow rate at cold start	19,98 m ³ /h		
8 Vapor press. at tW / tS	0,2 / bar	NPSH	System 9,67 m	Total. abs. power at cold start	12,89 kW		
9 pH value	7	required	2,81 m	Dissipation cold	4,343 kW		
Installation / Environment							
10 Building / Outside	Gebäude	Altitude	< 1000 m	Amb. Temp. min	20 / 40 °C		
11 under roof yes/no	Ja / Yes	ATEX aggregate category	not Atex	rel. Humidity	<35 %		
Pump							
12 Impeller-Ø / RJS	215 / 144 mm	Pressure rating	PN 16	Pressure rating	PN 16		
13 Impeller type	Radial impeller	Suction port	nom. diam. DN 50	Delivery port	nom. diam. DN 32		
14 direction of rotation	right	Standard	EN 1092-2	Standard	EN 1092-2		
15 Single head pump	X 1	Specifying calming suction side = min.	250 mm				
Accessories							
16 Motor	Magnetic drive	Base plate					
17 Make	HOYER	Type	HMC2 160M2-2	Description	135-060		
18 Specific design	IE 2 / 50 Hz / Pole pairs 1	Number of poles	2	rated load torque	155 Nm	Specific design	
19 Rated power	15 kW	Degree of p	IP 55	Magnetic drive pow	33 kW	Length	mm
20 Rated current	27 A	Frequency	50 ± 2 % Hz	Length of magnet	60 mm	Width	mm
21 1-phase / 3-phase	3-	Voltage	400 ± 5 % V	Diameter	135 mm		
22 Rated speed	2930 1/min	Mounting	IM B35			name plate	
23 Motor flange ø 350 mm	Sound pressure level dB(A)					links	
24							
25	terminal box, motor	obc					
Materials							
26 Volute casing	EN-GJS-400-15	Impeller	EN-GJL-250				
27 Casing cover	EN-GJS-400-15	Bracket	EN-GJS-400-15				
28 Shaft	1.4122	Bearing complete	SIC1.4122				
29							
30							
31							
32							
Tests and Inspections							
33 Material Tests	Test	2) Certificate	Other Tests	Tests and Inspections	2) Certificate	Qty	
34 Volute casing	keine	kein	Hydrost. Pressure Test	Intern	kein	alle	
35 Impeller	keine	kein	Gas Pressure Test	3) Intern	kein	alle	
36 Casing cover	keine	kein	Performance curve	4)	Keine	alle	
37 Bracket	keine	kein	NPSH-Measurement	Keine	kein	alle	
38 Shaft	keine	kein	Final check	Intern	kein	alle	
39			vibration	Keine	kein	alle	
40			temperature	Keine	kein	alle	
41			Max. operating pressure	16 bar / 20°C X Factor 1,5 test time 10 min			
Shipping data 5)							
42 Net weight appr.	kg	Gross weight appr.	kg	pump color	motor color		
Documentation							
43 Dimensional drwg.	Cross sect. drwg.	performance curve No.	Oper. & Instruct. Man.	Other (see attached)	Qty		
44 RD 8.30. xxx	E 4022. xxx	KL 8.30.198	DE 1096.0972		1		
Remarks							
45						motor article	
46	1) motor supplement corresponds to ISO 9908						
	2) according to EN 10204						
	3) valve casting & cover						
	4) without NPSH test						
	5) scope of deliv. to price sheet						

Technical data sheet (example)



Characteristic curve (example)



Dimensional drawing (example)

Save projects

Interim configuration results such as characteristic curves, scale drawings or technical data sheets can be saved as a project and generated as a pdf file.

Order-related tests

Pressure tests

Speck carries out the tests below as standard:

Gas pressure test

The gas pressure test is used to prove that the components are leak-proof. All components that bear pressure are tested, such as the volute casing, casing cover and mechanical seal casing. The test is carried out with forming gas at 2 bar. The holding time is 15 minutes.

Hydrostatic pressure test

The hydrostatic pressure test is used to prove strength of the components and that the pump is leak-proof. The fully assembled pump is tested. The test is carried out with a hydrostatic test pressure based on prEN 12162; the hydrostatic test pressure corresponds to $1.5 \times$ the nominal pressure (PN16) at 20 °C. The holding time is 10 minutes.

If you want to use pressure tests according to different criteria, please enter them in the request.

Testing the performance

At the customer's request, Speck offers the following tests:

Hydraulic tests

Measurement according to DIN EN ISO 9906, Class II, Acceptance Class 2B, Edition March 2013

NPSH test

In this test, the suction-side pressure is gradually reduced until the decrease in the delivered head reaches 3 % at a constant flow rate. At least four flows are evaluated that are spread appropriately over the admissible operating range. The NPSH value is not a guarantee point.

Vibration test

Vibration test according to EN ISO 5199, Edition 2002

The vibration values are measured radially and vertically at every operating point on the bearing casing at the nominal speed and with the corresponding flow rate.

Temperature measurement

The measurement is taken on the motor-side bearing at operating temperature. The operating temperature and the ambient temperature at every operating point measured are documented.



Computer-controlled and fully automated test stands on the premises of Speck in Roth.

Measuring of hydraulics, power requirements, axial thrust, vibrations and NPSH values. Heads of up to 400 m and flow rates of up to 750 m³/h are possible.

Further data and notes

Standard conditions at site

- » Ambient temperature from -20 °C to +40 °C
- » Permissible altitude up to 1000 m above seal level

Deviations from the site conditions specified herein must already be disclosed in the inquiry.

Painting

The pumps are coated with highly heat-resistant white aluminium paint, colour code RAL 9006.

Dimensioning

Assessment of the maximum pump outlet pressure

The pump outlet pressure at the pump nozzle depends on

- » the pump inlet pressure
- » the maximum total head of the selected impeller diameter
- » the density of the medium to be pumped

The maximum pump outlet pressure $p_{2\max op}$ is calculated using the formula:

$$p_{2\max op} = p_{1\max op} + \rho \cdot g \cdot H \cdot 10^{-5}$$

With:


- $p_{2\max op}$ = maximum pump outlet pressure [bar]
- $p_{1\max op}$ = maximum pump inlet pressure [bar]
- ρ = density of the medium to be pumped [kg/m^3]
- g = gravitation constant [m/s^2]
- H = maximum total head at zero flow or at the peak of the pump's characteristic curve at the selected impeller diameter [m]

Pumps must be selected and operated in a way which ensures that the maximum pump outlet pressure does by no means exceed the maximum permissible operating pressure of the casing $p_{all w c}$ at operating pressure.

This also applies to commissioning while the discharge valve is closed (refer to diagram).

Pressure and temperature limitations



The maximum casing operating pressure $p_{all w c}$ of the pressure retaining parts depends on the operating temperature:



Maximum permissible casing operating pressure $p_{all w c}$

TOE-MN / MA – Characteristic curves

50 Hz





Bearing bracket 360

Bearing bracket 470

Ⓐ Casing with double volute

÷ Casing with centreline mounting

60 Hz

**Bearing bracket 360****Bearing bracket 470**


Casing with double volute



Casing with centreline mounting

TOE-MI – Characteristic curves



50 Hz



Bearing bracket 360

Size 40-160 with hydraulics A or B available


60 Hz

**Bearing bracket 360**

Size 40-160 with hydraulics A or B available

TOE-MN / MA – Dimensions and connections

Bearing bracket 360



Size	DNS	DS	tS	DND	DD	tD	a	bL	bR	h1	h2	b	m1	m2	n1	n2	x
32-160	50	165	20	32	140	15	80	116	121	132	160	50	100	70	240	190	110
32-200	50	165	20	32	140	18	80	123	135	160	180	50	100	70	240	190	110
32-250	50	165	20	32	140	18	100	152	163	180	225	65	125	95	320	250	110
40-160	65	185	20	40	150	18	80	123	129	132	160	50	100	70	240	190	110
40-200	65	185	20	40	150	18	100	127	141	160	180	50	100	70	265	212	110
40-250	65	185	20	40	150	18	100	151	160	180	225	65	125	95	320	250	110
50-160	65	185	20	50	165	20	100	123	136	160	180	50	100	70	265	212	110
50-200	65	185	20	50	165	20	100	130	148	160	200	50	100	70	265	212	110
50-250	65	185	20	50	165	20	100	157	170	180	225	65	125	95	320	250	110
65-160	80	200	22	65	185	20	100	124	151	160	200	65	125	95	280	212	110
65-200	80	200	22	65	185	20	100	136	164	180	225	65	125	95	320	250	110
80-160	100	220	24	80	200	22	125	139	174	180	225	65	125	95	320	250	110

Utility connections

P1 G 1/4 Manometer connection pressure-side (without bore)

P2 G 1/8 Manometer connection suction-side (without bore)

D1 G 3/8 Drainage volute casing

T1 G 1/4 Temperature sensor PT 100 (magnetic coupling 110 / 135 / 165)

T2 G 1/4 Temperature sensor PT 100 (magnetic coupling 75)

T3 G 1/4 Temperature sensor PT 100 (magnetic coupling 60)


① Fitting key DIN 6885

② Feet applicable for motor design B5 only

Flange dimensions → page 16

TOE-MN / MA – Dimensions and connections

Bearing bracket 470



Size	DNS	DS	tS	DND	DD	tD	a	bL	bR	h1	h2	b	b1	m1	m2	n1	n2	øs1	x
65-250	80	200	22	65	185	20	100	233,5	233,5	200	250	80	18	160	120	360	280	18	140
80-200 ¹	100	220	24	80	200	22	125	162,5	191	180	250	65	15	125	95	345	280	14	140
80-250 ²	100	220	24	80	200	22	125	181	206,5	200	280	80	18	160	120	400	315	18	140
100-160	125	254	26	100	230	25	125	233,5	233,5	200	280	80	18	160	120	360	280	18	140
100-200 ³	125	254	26	100	230	25	125	233,5	233,5	200	280	80	18	160	120	360	280	18	140
100-250 ³	125	254	26	100	230	25	140	230	230	225	280	80	18	160	120	400	315	18	140
125-200 ³	150	285	26	125	254	26	140	262	262	250	315	80	18	160	120	400	315	18	140

¹ Casing with feet resp. without centreline mounting

² Casing with feet – as of 2015 casing with centreline mounting

³ Casing with double volute

Utility connections

P1 G 1/4 Manometer connection pressure-side (without bore)

P2 G 1/8 Manometer connection suction-side (without bore)

D1 G 3/8 Drainage volute casing

T1 G 1/4 Temperature sensor PT 100 (magnetic coupling 110 / 135 / 165)

① Fitting key DIN 6885


② Feet applicable for motor design B5 only

Flange dimensions → page 16

TOE-MI – Dimensions and connections

Bearing bracket 360

TOE-MI



Size	Casing	DNS	DND	a	DD	DS	tD	tS	bL	bR	h1	h2	k	x
40-160	INA	40	40	97	150	150	20	20	116	116	200	190	395,5	110
40-160	INB	40	40	97	150	150	20	20	116	116	180	160	395,5	110
40-200	INA	40	40	93	150	150	20	20	135	135	200	190	399,5	110
50-200	INA	50	50	102	165	165	21	21	126	139	220	205	399,5	110
50-200	INB	50	50	92	165	165	21	21	126	139	200	180	409,5	110
65-200	INA	65	65	112	185	185	23	23	131	151	240	225	400,5	110
65/80-200	INB	80	80	112	200	200	23	23	131	151	255	225	400,5	110


Utility connections

- P1 G 1/4 Manometer connection pressure-side (without bore)
 P2 G 1/8 Manometer connection suction-side (without bore)
 D1 G 3/8 Drainage volute casing
 T1 G 1/4 Temperature sensor PT 100 (magnetic coupling 110 / 135 / 165)
 T2 G 1/4 Temperature sensor PT 100 (magnetic coupling 75)
 T3 G 1/4 Temperature sensor PT 100 (magnetic coupling 60)

Flange dimensions

Flanges in acc. with DIN EN 1092-2			
DN	ØD1	ØD3	Holes
32	100	19	4
40	110	19	4
50	125	19	4
65	145	19	4
80	160	19	8
100	180	19	8
125	210	19	8
150	240	23	8

Flanges in acc. with DIN EN 1092-2, drilled in acc. with ANSI 150 lbs			
DN	ØD1	ØD3	Holes
32	88,9	16	4
40	98,6	16	4
50	120,7	19	4
65	139,7	19	4
80	152,4	19	4
100	190,5	19	8
125	215,9	22	8
150	241,3	22	8



Interchangeability of parts

All series including the versions with mechanical seal (→ brochure TOE-GN/GA/GI series) offer a high degree of interchangeability.

Same components within TOE-MN/MA/MI series




Compare only numbers within one **row**:

1 and **1** = same number means same component

1 and **2** and ... = different numbers mean different components


Component	No.	Series	Pump size																		
			32-160	32-200	32-250	40-160	40-200	40-250	50-160	50-200	50-250	65-160	65-200	80-160	80-200	80-250	100-160	100-200	100-250	125-200	
Bearing bracket complete ¹	-	MN MA MI	1	2	1	2	1	2	1	2	1	2	1	3	4	3	5	4	3	4	
Volute casing	102	MN MA -	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
Volute casing	102	- - MI				20	21		22			23									
Casing cover	161	MN MA MI	1	2	1	2	1	2	1	2	1	2	1	3	4	3	5	4	3	4	
Shaft	211	MN MA MI						1											2		
Impeller	230	MN MA -	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
Impeller	230	- - MI				1	20		5			8									
Sleeve bearing ¹	310	MN MA MI						1 ¹										2 ¹			
Bearing casing / rolling bearing / bearing cover	330 / 320 / 360	MN - -							1									2			
Bracket	341	MN MA MI							1									2			
Flat gasket	400	MN MA MI							1									2			
Flat gasket	400.1	MN MA -			1			1			1										
Flat gasket	400.2 / 400.3	MN MA MI							1 ¹									2 ¹			
Counter flange	720	MN MA -			1		1			1											
Coupling insert ¹	843	MN MA MI						1 ¹									2 ¹				
Magnetic coupling complete ¹	847	MN MA MI						1 ¹									2 ¹				
further parts	-	MN MA MI						1									2				

¹ Interchangeable with identical sizes of magnetic coupling only.



Pumps for heat transfer technology

*Centrifugal pumps
with mechanical seal*



Modular system

TOE-TOE-GN/GA/GI and TOE-MN/MA/MI series mean a consistent designed modular system. Hydraulics and the main part of the used components are identical and interchangeable.

TOE-GN/GA/GI Series

These pumps are designed for circulating organic or synthetic heat transfer oils in heat transfer plants in acc. with DIN 4754, as well as hot water.

Suitable for media to be pumped with little non-abrasive contaminations

	Thermal oil versions	Hot water versions
Media	Heat transfer oil / thermal oil	Water
T _{min}	- 40 °C	-
T _{max}	+ 350 °C	+ 160 °C, + 180 °C on request
Casing	Spheroidal graphite cast iron	Spheroidal graphite cast iron or stainless steel
Nominal pressure	PN 16	PN 25 higher pressures on request
H _{max} (2900 min ⁻¹)	100 m	90 m
Q _{max} (2900 min ⁻¹)	550 m ³ /h	12 m ³ /h (200 l/min) 24 m ³ /h (400 l/min) on request
ATEX	II 3G c TX	II 2G c b TX

Description in full length → see brochure TOE-GN/GA/GI series

*Regenerative turbine pumps
with magnetic coupling*



NPY-MK and CY-MK Series

Tried and tested and compact close-coupled pumps with top/top casings and magnetic coupling. Developed for transporting and circulating organic or synthetic heat transfer oils and hot water. Suitable for pumped media with low amounts of non-abrasive impurities. Suitable for the delivery of gas shares due to the principle of delivery.

	Thermal oil versions	Hot water versions
Media	Heat transfer oil / thermal oil	Water
T _{min}	- 100 °C	-
T _{max}	+ 350 °C + 400 °C on request	+ 200 °C higher temp. on request
Casing	Spheroidal graphite cast iron or stainless steel	
Nominal pressure	PN 25	higher pressures on request
H _{max} (2900 min ⁻¹)	90 m	
Q _{max} (2900 min ⁻¹)	12 m ³ /h (200 l/min) 24 m ³ /h (400 l/min) on request	
ATEX	II 2G c b TX	

Compact, robust, durable and safe

Regenerative turbine pumps with magnetic coupling from Speck have been used in a wide range of systems and assemblies successfully for many years. The compact design requires minimal installation space and reduces the weight. The perfected pumps also impress with the small number of extremely high-quality parts.

Robust sleeve bearings made from SiC and ceramic shafts guarantee a long lifetime and are free from leakage and maintenance-free thanks to magnetic couplings.

On request, Speck can also develop special designs for special media or with different hydraulics. Please contact us.

Your notes

A large grid of squares, approximately 20 columns by 25 rows, designed for writing notes or drawing.

Your notes

A large grid of empty squares, intended for users to write their own notes.

Representatives

D Germany

Deutschland Ost
Huckauf Ingenieure GmbH
Rathausstraße 5
09244 Lichtenau
Tel.: +49 37208 660 80
Fax: +49 37208 660 77
info@huckauf.de
www.huckauf.de

Berlin
Huckauf Ingenieure GmbH
Fontanepromenade 17
10967 Berlin
Tel.: +49 30 890 959 92
Fax: +49 30 890 959 91
info@huckauf.de
www.huckauf.de

Norddeutschland
Ingenieure Willy Wandach GmbH
Flurstraße 105
22549 Hamburg
Tel.: +49 40 398 624 0
Fax: +49 40 398 624 28
info@speck-nord.de
www.speck-nord.de

Hannover, Kassel
IVT – Pumpen GmbH
Zum Wissfeld 1A
31749 Auetal
Tel.: +49 5752 929 597
Fax: +49 5752 929 599
Mobile: +49 172 511 699 9
info@ivt-pumpen.de
www.ivt-pumpen.de

Köln
Huckauf Ingenieure GmbH
Grillenpfad 28
40764 Langenfeld
Tel.: +49 2173 914 560
Fax: +49 2173 914 588
info@huckauf.de
www.huckauf.de

Bayern, Baden-Württemberg
Speck Pumpen
VERKAUFSGESELLSCHAFT GmbH
Hauptstraße 1 – 3
91233 Neunkirchen a. Sand
Tel.: +49 9123 949 – 0
Fax: +49 9123 949 – 260
info@speck-pumps.com
www.speck-pumps.com

Service

Deutschland Mitte
FSE Fluid Systems Erfurt
Poeler Weg 6
99085 Erfurt
Tel.: +49 361 550 715 0
Fax: +49 361 550 715 19
info@fluidsystems.org
www.fluidsystems.org

Köln
Arpuma GmbH
Ottostrasse 10
50170 Kerpen
Tel.: +49 2273 953 300 0
Fax: +49 2273 953 300 20
info@arpuma.de
www.arpuma.de

International

A Austria
Tuma Pumpensysteme GmbH
Ettengasse 12
1230 Wien
Tel.: +43 191 493 40
Fax: +43 191 414 46
contact@tumapumpen.at
www.tumapumpen.at

AUS Australia
Pump Solutions Australasia
Unit 1
7 Besserman Way
Wangara, WA 6065
P.O. Box 1811
Wangara DC, WA 6947
Tel.: +61 8 9408 1544
Fax: +61 8 9408 1644
mike@pumpsolutions.com.au
www.pumpsolutions.com.au

Pump Systems Australia
Factory 2
21 London Drive
Bayswater / Melbourne
Victoria 3153
Tel.: +61 397 623 100
Fax: +61 397 623 188
sales@pumpsystemsaustralia.com.au

B Belgium

Heat transfer pumps / Pompe pour fluid thermique
FLOWMOTION BVBA
Mergelweg 3
1730 Asse
Tel.: +32 2 309 67 13
Fax: +32 2 309 69 13
info@flowmotion.be
www.flowmotion.be

SPECK - Pompen Belgie N.V.
Bierweg 24
9880 Aalter
Tel.: +32 937 530 39
Fax: +32 932 500 17
info@speckpompen.be
www.speckpompen.be

BG Bulgaria

EVROTEC OOD
54 A, Manastirska Str.
1111 Sofia
Tel.: +359 2 971 32 73
Fax: +359 2 971 22 88
office@evrotech.com
www.evrotech.com

CH Switzerland

Speck Pumpen Subsidiary
Speck Pumpen Industrie GmbH
Bürglenweg 4
8854 Galgenen
Tel.: +41 554 425 094
Fax: +41 554 425 094
info@speckswitzerland.com
www.speckswitzerland.com

Service & Service

HänyTec AG
Läffeld 2
6142 Gettnau
Tel.: +41 62 544 33 00
Fax: +41 62 544 33 10
contact@haenytic.ch
www.haenytic.ch

Service

MEYER ARMATUREN PUMPEN GMBH
Rigakustrasse 19
5610 Wohlen
Tel. +41 56 622 77 33
Fax +41 56 622 77 60
info@meyer-armaturen.ch
www.meyer-armaturen.ch

CN China

Speck Pumpen Subsidiary

Jiashan SPECK PUMPS
Systemtechnik Ltd.
No. 57, Hong Qiao Rd.,
No. 4 Economic Developing Zone,
314100 Jiashan Xian,
Zhejiang Province

Tel.: +86 573 847 312 98
Fax: +86 573 847 312 88
steveche@speck-pumps.cn
www.speck-pumps.cn

CZ Czech Republic

Sigmat spol.s.r.o.
Košmonautů č.p. 1103/6a
77200 Olomouc
Tel.: +420 585 231 070
Fax: +420 585 227 072
sigmet@sigmet.cz
www.sigmet.cz

DK Denmark

Pumpegruppen a/s
Lundtoftegårdsvænge
2800 Lyngby
Tel.: +45 459 371 00
Fax: +45 459 347 55
info@pumpegruppen.dk
www.pumpegruppen.dk

E Spain

Speck Pumpen Subsidiary

SPECK BOMBAS INDUSTRIALES, S.L.U.
Trafalgar, 53 despatio 6
Centro de Negocios CNAF
46023 Valencia
Tel.: +34 963 811 094
Fax: +34 963 811 096
Mobile: +34 618 376 241
speck-spain@terra.com
www.speck.de

F France

Speck Pumpen Subsidiary

Speck Pompes Industries S.A.
Z.I. Parc d'Activités du Ried
4, rue de l'Energie
B.P. 227
67727 Hoerdt Cedex
Tel.: +33 3 88 68 26 60
Fax: +33 3 88 68 16 86
info@speck.fr

GB Great Britain

Speck ABC UK Ltd
AreenA House
Moston Road,
Elworth, Sandbach
Cheshire CW11 3HL
Tel.: +44 844 764 063 2
Fax: +44 844 764 063 4
admin@speck-abc.com
www.speck-abc.com

GR Greece

SPECK Hellas
Salaminos St. 54
17676 Kallithea
Tel.: +30 210 956 500 6
Fax: +30 210 957 747 3
grema@speckhellas.gr

I Italy

Centrifugal pumps / Pompe centrifughe
Speck Industries S.r.l.
Via Garibaldi, 53
20010 Canegrate (MI)
Tel.: +39 0331 405 805
Mobile: +39 339 16 59 440
info@speckindustries.it
www.speckindustries.it

IL Israel

Ambi-Tech
Electronics Engineering Ltd.,
20 Ta'as st.;
Industrial Area, Kfar-Saba
PO. Box 50
Kfar-Saba 44425
Tel.: +972 976 775 00
Fax: +972 976 774 00
Arie.Weiss@PWeiss.d2g.com
www.pweiss.co.il

Small pumps / heat transfer pumps :

Ringel Brothers (1973) Ltd.
134 Hertzel St.
P.O. Box 5148
Tel-Aviv 66555
Tel.: +972 368 255 05
Fax: +972 368 220 41
Mobile: +972 544 623 095
mringle@ringel-bros.co.il
www.ringel-bros.co.il

IND India

Flux Pumps India Pvt. Ltd.
427/A-2, Gultekdi Industrial Estate
Near Prabhat Printing Press
Pune – 411 047, Maharashtra
Tel.: +91 020 2427 1023
Fax: +91 020 2427 0689
Mobile: +91 98504 03114
kiran.kadam@flux-pumps.in
www.flux-pumps.in

J Japan

Rodateq, Inc.
Suite 301 Oka Bldg.
2 – 1 – 16 Kyomachibori, Nishiku
550 – 0003 Osaka
Tel.: +81 664 441 940
Fax: +81 664 449 050
info@rodateq.co.jp
www.rodateq.co.jp

Rodateq, Inc.

Tokyo Branch
No. 408, 3 - 22 - 12
Highashi Ikekuburo, Toshima - ku
170-0013 Tokyo
Tel.: +81 359 798 818

Fax: +81 359 798 817
roda-t@yo.rim.or.jp
www.rodateq.co.jp

L Luxembourg

Heat transfer pumps / Pompe pour fluid thermique
FLOWMOTION BVBA
Mergelweg 3
1730 Asse

Tel.: +32 2 309 67 13

Fax: +32 2 309 69 13

info@flowmotion.be

www.flowmotion.be

MAL Malaysia

Leesonmech
Engineering (M) Sdn. Bhd.
No. 18 Jalan 18, Taman Sri Kluang,
86000 Kluang, Johor
Tel.: +607 777 105 5
Fax: +607 777 106 6
sales@leesonmech.com
www.leesonmech.com

N Norway

Ingv. Pjerdrum A/S
P.O. Box 154
Nye Vakasvei 28
1360 Nesbru
Tel.: +47 667 756 00
Fax: +47 667 756 01
Pg-pumps@perjerdum.no
www.pg-marinegroup.com

NL Netherlands

Centrifugal pumps / Centrifugadelpompen
Speck Pompen Nederland B.V.
Businesspark 7Poort
Stationspoort 10
6902 KG Zevenaar
Tel.: +31 316 331 757
Fax: +31 316 528 618
info@speck.nl
www.speck.nl

Vacuum pumps / Vacuümpompen

DOVAC B.V.
Meer en Duin 228
2163 LH Lisse
Tel.: +31 252 423 363
Fax: +31 252 417 946
info@dovac.nl
www.dovac.nl

Heat transfer pumps / Pompe pour fluid thermique

FLOWMOTION BVBA
Mergelweg 3
1730 Asse
Tel.: +32 2 309 67 13
Fax: +32 2 309 69 13
info@flowmotion.be
www.flowmotion.be

NZ New Zealand

MacEwans Pumping Systems Ltd.
19 Ride Way
North Harbour Industrial Estate
Tel.: +64 941 548 60
Fax: +64 941 548 68
pumps-ak@macewans.co.nz
www.macewans.co.nz

P Portugal

Ultra Controlo
Projectos Industriais, Lda.
Quinta Lavi – Armação 8
Abrunheira
27 089 Sintra
Tel.: +351 219 154 350
Fax: +351 219 259 002
info@ultra-controlo.com
www.ultra-controlo.com

PL Poland

E.A. Krupinski Elzbieta Krupinska
ul. Przymiarki 4A
31-764 Krakow
Tel. / Fax: +48 126 455 684
biuro@krupinski.krakow.pl
www.krupinski.krakow.pl

RC Taiwan

Speck Pumpen Subsidiary
Speck Pumps Technology Taiwan Ltd.
2FL, no. 153, Sec. 2
Datong Rd., Xizhi District
New Taipei City
Tel.: +886 286 926 220
Fax: +886 286 926 759
Mobile: +886 936 120 952
speck886@ms32.hinet.net
www.speck-pumps.com.tw

RCH Chile

W & F Ingeniería Y Maquinaria S.A.
Felix de Amesti 90, Piso 6
Las Condes, Santiago
Tel.: +56 220 629 43
Fax: +56 220 630 39
rwender@tie.cl

RI Indonesia

PT Roda Rollen Indonusa
Kompleks Pertokoan Glodok
Jaya No. 30
Jl. Hayam Wuruk,
Jakarta - Pusat
Indonesia, 11180
Tel.: +6221 659 922 528
Fax: +6221 380 595 9
rudy@rodarollenindonesia.com

ROK Corea

J.C. International Inc.
2F, Bilkem Bldg. 108,
Yanghwa-Ro, Mapo-Gu,
121-893 Seoul
Tel.: +82 232 628 00
Fax: +82 232 569 09
jclee@cint.co.kr
www.jcint.co.kr

RO Romania

S.C. Gimsid S.R.L.
Str. Arcului nr. 9, Arp.2
021031 Bucuresti
Tel.: +40 21 2118701
Fax: +40 21 2102675
gimsid@gimsid.ro
www.gimsid.ro

RUS Russia

LLC Firm Kreoline
Yunost str., 5/3
Moscow 11395
Tel: +7 495 737 321 4
Fax: +7 495 769 844 0
Mobile: +7 495 505 198 8
Info@kreoline.ru
www.kreoline.ru

S Sweden

Hugo Tillquist AB
P.O.Box 1120
16422 Kista
Tel.: +46 859 463 200
Fax: +46 859 136 95
Info@tillquist.com
www.tillquist.com

SK Slovakian Republic

→ Czech Republic (CZ)

SLO Slovenia
SLOTEH Branko Gabric s.p.
Zagrebška cesta 20
2000 Maribor
Tel.: +38 624 614 460
Fax: +38 624 614 465
branko.gabric@amis.net
www.sloteh.si

SGP Singapore

→ Malaysia (MAL)

TH Thailand

Speck Pumpen Subsidiary
Pump Systems Flux & Speck Co. Ltd.
181/4 Soi Anamai
Srinakarin Road
Suanluang Bangkok 10250
Tel.: +662 320 256 7
Fax: +662 322 248 6
thienchai@fluxspeck.com
www.fluxspeck.com

TR Turkey


Speck Pompa
San ve Tic. Ltd. Sti.
Girne Mah., Küçükali Is Merkezi
B Blok No.12 Maltepe
34852 İstanbul
Tel.: +90 216 375 750 5
Fax: +90 216 375 753 3
Mobil: +90 532 293 01 4
speck@speckpompa.com.tr
www.speckpompa.com.tr

USA USA

Speck Pumpen Subsidiary
Speck Industries LP
301 Veterans Blvd
Rutherford
NJ 07070
Tel.: +1 201 569 3114
Fax: +1 201 569 9607
Info@speckamerica.com
www.speckamerica.com

ZA Rep. South Africa

AQUAPUMP (Pty) Ltd.
Unit 54
APD Industrial park
Kelvin street
Kya Sand
Tel.: +27 11 080 600
Fax: +27 865 864 151
Mobile: +27 824 509 078
cliff@aquapump.co.za
www.aquapump.co.za



Speck Pumpen Systemtechnik GmbH
Postfach 1453 · 91142 Roth / Germany
Regensburger Ring 6-8 · 91154 Roth / Germany
Tel.: +49 (0) 91 71 809 - 0
Fax: +49 (0) 91 71 809 - 10
info@speck.de
www.speck.de